

Specifications	4X4 2.8G	4X4 2.8G AT
Transmission	6 MT with iMT	6 AT with Sequential Shift
Dimension		
Overall Length x Width x Height (mm.)	5,330 x 1,855 x 1,815	5,330 x 1,855 x 1,815
Wheelbase (mm.)	3,085	3,085
Tread Front/Rear (mm.)	1,535 x 1,550	1,535 x 1,550
Min. Ground Clearance (mm.)	217	217
Deck Inside Length x Width x Height (mm.)	1,555 x 1,540 x 480	1,555 x 1,540 x 480
Engine		
Model	1GD-FTV (High)	1GD-FTV (High)
Type	4 cyl 16 valve DOHC VN Turbo Intercooler	4 cyl 16 valve DOHC VN Turbo Intercooler
Displacement (cc.)	2,755	2,755
Bore x Stroke (mm.)	92.0 x 103.6	92.0 x 103.6
Compression Ratio	15.6 : 1	15.6 : 1
Max. Power [kW(PS)/rpm]	130(177)/3,400	130(177)/3,400
Max. Power (Nm/rpm)	420/1,400-2,600	450/1,600-2,400
Stop and start system with evaporator for air conditioning temperature control	-	-
Fuel Supply System	Direct Injection Common-rail	Direct Injection Common-rail
Fuel Capacity (L.)	80	80
Fuel Type	Diesel	Diesel
Transmission and Chassis		
Transmission	4X4 with Differential Lock at rear axle	4X4 with Differential Lock at rear axle
Transmission System	6MT with iMT	6AT with Sequential Shift
Gear Ratio 1	4.784	3.6
Gear Ratio 2	2.423	2.09
Gear Ratio 3	1.443	1.488
Gear Ratio 4	1	1
Gear Ratio 5	0.826	0.687
Gear Ratio 6	0.643	0.58
Reverse Gear Ratio	4.066	3.732
Final Gear Ratio	3.583	3.909
Front Suspension	Double wishbone with stabilizer	Double wishbone with stabilizer
Rear Suspension	Rigid type	Rigid type
Front Brake	Disc brake / Ventilated disc	Disc brake / Ventilated disc
Rear Brake	Drum brake	Drum brake
Steering System	Rack & Pinion power Steering	Rack & Pinion power Steering
Min. Turning Radius (m.)	6.4	6.4
Tyre	265/65R 17 All Terrain	265/65R 17 All Terrain
Wheel	Alloy 17"	Alloy 17"
Spare Tire	Steel wheel 265/65R 17 All Terrain	Steel wheel 265/65R 17 All Terrain